


Extruded Aluminum T-Bar 						
Product No.	Side A (mm)	Side B (mm)	Thickness (mm)	Weight(kg/m)	Extrusion Press Capacity	Alloy & Temper
ZWCT-34	14	5	A=2.5/B=7.5	0.538	500T	6063-T5
SYSZ-31	10.4	8.05	2	0.088	500T	6063-T5
ZW_D030744	15	15	2	0.151	500T	6060 T66
ZW_D055020	15	15	1.5	0.115	500T	6060-T66
ZW_D010083	30	15	2	0.232	500T	6060-T66
ZWGYC-4314	10.8	15.6	A=1.2/B=4.8	0.220	500T	6063-T5
ZW_D031016	20	20	2	0.205	500T	6060-T66
ZW_D030360	25	25	2	0.259	500	6060-T66
ZW_D030745	25	25	3	0.381	660T	6060 T66
ZW_D031467	25	25	1.6	0.209	500T	6063-T6
ZW_D010866	40	25	2	0.340	660T	6060-T66
ZW_D061169	40	25	3	0.502	660T	6060-T66
ZW_D031919	25.4	25.4	0.9	0.121	500T	6063-T5
ZW_D011870	25.4	25.4	3.18	0.408	660T	6063-T6
ZW_D011875	50.8	25.4	3.18	0.626	880T	6063-T6
ZW_D030746	30	30	2	0.313	660T	6060-T66
ZW_D070629	30	30	3	0.462	660T	6060-T66
ZW_D030899	50	30	3	0.634	880T	6060-T66
ZW_D061170	50	30	4	0.821	880T	6060-T66
ZW_D031017	60	30	4	0.929	880T	6060-T66
ZWYF-12	50	32	3.2	0.692	880T	2024-T3
ZW_D030748	35	35	3	0.543	660T	6060-T66
ZW_D060563	35	35	2	0.367	660T	6060-T66
ZW_D080599	38.1	38.1	6.35	1.198	1250T	6082-T6
ZW_D010056	20	40	2	0.313	660T	6060-T66
CHD_A000607	40	40	2	0.421	660	6060-T66
ZW_D020525	40	40	4	0.821	880	6060-T66
ZW_D030584	40	40	5	1.013	880T	6060-T66
ZW_D070501	40	40	3	0.624	880T	6060-T66
ZWGYC-5273	40	40	4	0.838	880T	6082-T6
ZW_D010001	60	40	5	1.283	1250T	6060-T66
ZW_D011306	60	40	4	1.037	880T	6060-T66
ZW_D030898	60	40	4	1.055	1250T	6060-T66
ZW_D011256	77	40	A=4/B=5	1.317	1250T	6060-T66
CBXC-65	25	50	A=4/B=3	0.645	880T	6082-T6
ZW_D010043	50	50	3	0.786	880T	6060-T66
ZW_D020535	50	50	4	1.037	880	6060-T66
ZW_D030581	50	50	2	0.529	660T	6060-T66
ZW_D031039	50	50	6	1.523	1250T	6060-T66
ZW_D060812	50	50	5	1.283	1250T	6060-T66
ZW_D061060	50	50	3	0.786	880T	6060-T66
ZWGYC-5274	50	50	4	1.054	880T	6082-T6
ZW_D020618	60	50	2.5	0.726	880	6060-T66
ZW_D031020	80	50	5	1.688	1250T	6060-T66
CHD_A000262	100	50	2	0.799	1250	6063-T66
ZW_D020622	110	50	2	0.853	880	6060-T66
CHD_A000261	120	50	2	0.907	1250	6063-T66
ZW_D011871	25.4	50.8	3.18	0.626	880T	6063-T6
ZW_D080601	50.8	50.8	3.18	0.845	880T	6063-T6
CBXC-50	50	60	4	1.055	880T	6082-T6
CBXC-52	50	60	A=6/B=4	1.411	1250T	6082-T6
CBXC-71	50	60	A=5/B=4	1.274	1250T	6082-T6
ZW_D030983	60	60	3	0.948	880T	6060-T66
ZW_D060411	60	60	4	1.253	1250T	6060-T66
ZW_D070730	60	60	6	1.847	1250T	6060-T66
ZW_D030476	100	60	5	2.093	1800T	6060-T66
CBXC-51	50	70	A=8/B=4	1.768	1250T	6082-T6
ZW_D012507	50	75	8	2.527	2000T	6082-T6
ZW_D062070	75	75	6	2.333	2000T	6063-T5
ZW_D011876	76.2	76.2	6.35	2.504	2000T	6063-T6

ZW_D031019	50	80	4	1.361	1250T	6060-T66
ACC1003105G030	50	80	5	1.716	1250T	6005A-T6
CHD_A000411	80	80	4	1.685	1250T	6060-T66
ZW_D011302	80	80	6	2.495	2000T	6060-T66
AJC1056831G030	100	80	15	6.887	3600T	600A-T6
ZW_D062092	50.8	82.67	6.35	2.182	1800T	6005A-T6
LGSW-26	43.27	99	A=3/B=6	1.906	1250T	6063-T5
CBXC-56	45	100	A=8/B=5	2.232	2000T	6082-T6
ZW_D012486	50	100	5	1.957	1800T	6060-T6/6082-T6
ZW_D020526	60	100	5	2.093	1800	6060-T66
ZW_D010322	100	100	6	3.142	2750T	6060-T66
ZW_D030749	100	100	10	5.130	3600T	6060-T66
CCD00000444079	50	105	8	3.182	2750T	6005A-T4
ZJ-M80104	60	120	A=6/B=9	3.742	2750T	6061-T6
ZWGYC-2933	80	120	A=2.5/B=2	1.179	1800T	6063-T5
ACC1003030G030	80	120	6	3.172	2750T	6005A-T6
RFT-72	120	120	6	3.820	2000	6082-T6
ZW_D010240	120	120	8	5.011	2750T	6060-T66
YDKM-BMR-117	78	135	8	4.427	2750T	6063-T6
CBXC-49	80	139	A=8/B=5	3.515	2750T	6082-T6
ZWGYC-3706	140	160	10	7.917	3600T	6061-T6
ZWGYC-2267	80	180	7	4.948	3150T	6061-T6
RFT-81	90	200	8	6.207	3600T	6061-T6
ZWQC-YQJ7-06	162	208	A=8/B=13.5	11.252	7500T 440*260	6082-T6
BH-042	40	261	4	3.209	3600T	6063-T6